



**Paradigm**

THE ULTIMATE IN SOUND FOR MUSIC AND HOME THEATER™



## CC-290

Design	4-driver, 3-way center channel, MagneShield™††
Crossover	2nd-order electro-acoustic at 2.5 kHz, 2nd-order electro-acoustic at 250 Hz (bass drivers)
High-Frequency Driver	25-mm (1 in) H-PTD™ dome, ferro-fluid cooled
Midrange Driver(s)	115-mm (4-1/2 in) M-ICP™ cone, 25-mm (1 in) voice coil, ferro-fluid cooled, GRIP™ chassis
Bass Driver	Two 165-mm (6-1/2 in) carbon-infused polypropylene cones, 25-mm (1 in) voice coils, die-cast heatsink chassis
Low Frequency Extension	46 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 80 Hz - 20 kHz
30° Off-Axis	±2 dB from 80 Hz - 17 kHz
Sensitivity - Room / Anechoic	94 dB / 91 dB
Suitable Amplifier Power Range	15 - 175 watts
Maximum Input Power	120 watts
Impedance	Compatible with 8 ohms
Internal Volume	22.8 L / 0.80 cu ft
Height, Width, Depth	19.8 cm x 67.9 cm x 29 cm
	7-13/16 in x 26-3/4 in x 11-7/16 in
Weight (Unpacked)	14.5 kg / 32 lb each
Finishes	Wengé, Cherry, Rosenut, Black Ash
Paradigm® Stand (sold sep.)	Paradigm® J-18C