



**Paradigm**

THE ULTIMATE IN SOUND FOR MUSIC AND HOME THEATER™



### Cinema™ 330

Design	5-driver, 2-1/2 way acoustic suspension, mineral-filled polymer enclosure, MagneShield™††
Crossover	4th-order electro-acoustic at 2.0 kHz, 2nd-order electro-acoustic at 400 Hz
High-Frequency Driver	25-mm (1 in) PTD™ dome, aluminum heatsink
Bass / Midrange Driver(s)	Two 115-mm (4-1/2 in) ICP™ cones, die-cast chassis
Bass Driver	Two 115-mm (4-1/2 in) black polypropylene cones, die-cast chassis
Low Frequency Extension	80 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 110 Hz - 20 kHz
30° Off-Axis	±2 dB from 110 Hz - 15 kHz
Sensitivity - Room / Anechoic	94 dB / 91 dB
Suitable Amplifier Power Range	15 - 120 watts
Maximum Input Power	100 watts
Impedance	compatible with 8 ohms
Internal Volume	5.5 L / 0.20 cu ft
Height, Width, Depth	62.2 cm x 16.1 cm x 10.5 cm
	24-1/2 in x 6-5/16 in x 4-1/8 in
Weight	5.7 kg / 12.6 lb each
Finishes	Silver, Black, Black Gloss
Matching Speaker Stand	LS-15, LS-25