



Paradigm

THE ULTIMATE IN SOUND FOR MUSIC AND HOME THEATER™



Cinema™ Micro

Design	2-driver, 2-way bookshelf / stand-mounted
Crossover	3rd-order electro-acoustic at 2.4 kHz
High-Frequency Driver	25-mm (1 in) PTD™ dome, ferro-fluid cooled
Bass / Midrange Driver(s)	140-mm (5-1/2 in) ICP™ cone, 25-mm (1 in) voice coil
Low Frequency Extension	55 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 89 Hz - 20 kHz
30° Off-Axis	±2 dB from 89 Hz - 15 kHz
Sensitivity - Room / Anechoic	90 dB / 87 dB
Suitable Amplifier Power Range	15 - 80 watts
Maximum Input Power	50 watts
Impedance	Compatible with 8 ohms
Height, Width, Depth	24.7 cm x 16.5 cm x 23.1 cm
(with grille)	9-3/4 in x 6-1/2 in x 9-1/8 in
Weight (Unpacked)	3.7 kg / 8.1 lb each
Finishes	Black
Paradigm® Stand (sold sep.)	Paradigm® S-30
On-Wall Brackets (sold sep.)	MB-60