



Paradigm

THE ULTIMATE IN SOUND FOR MUSIC AND HOME THEATER™



Mini Monitor

Design	2-driver, 2-way bass reflex, quasi-3rd-order resistive port
Crossover	2nd-order electro-acoustic at 2.0 kHz
High-Frequency Driver	25-mm (1 in) H-PTD™ dome, ferro-fluid cooled
Bass / Midrange Driver(s)	165-mm (6-1/2 in) M-ICP™ cone, 25-mm (1 in) voice coil, GRIP™ chassis
Low Frequency Extension	43 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 70 Hz - 20 kHz
30° Off-Axis	±2 dB from 70 Hz - 15 kHz
Sensitivity - Room / Anechoic	92 dB / 89 dB
Suitable Amplifier Power Range	15 - 100 watts
Maximum Input Power	80 watts
Impedance	Compatible with 8 ohms
Internal Volume	10.6 L / 0.37 cu ft
Height, Width, Depth	33.4 cm x 19 cm x 28.4 cm 13-1/8 in x 7-1/2 in x 11-3/16 in
Weight (Unpacked)	15.4 kg / 34 lb per pair
Finishes	Wenge, Cherry, Rosenut, Black Ash
Paradigm® Stand (sold sep.)	Paradigm® J-29, Paradigm® S-26