



## Monitor 7

Design	MagneShield™ optional for Black Ash only, 4-driver, 2-1/2-way bass reflex, quasi-3rd-order resistive port
Crossover	3rd-order electro-acoustic at 2.0 kHz, 2nd-order electro-acoustic at 700 Hz (lower bass drivers)
High-Frequency Driver	25-mm (1 in) H-PTD™ dome, ferro-fluid cooled
Bass / Midrange Driver(s)	140-mm (5-1/2 in) M-ICP™ cone, 25-mm (1 in) voice coil, GRIP™ chassis
Bass Driver	Two 140-mm (5-1/2 in) carbon-infused polypropylene cones, 25-mm (1 in) voice coils, GRIP™ chassis
Low Frequency Extension	41 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 54 Hz - 20 kHz
30° Off-Axis	±2 dB from 54 Hz - 15 kHz
Sensitivity - Room / Anechoic	94 dB / 91 dB
Suitable Amplifier Power Range	15 - 180 watts
Maximum Input Power	130 watts
Impedance	Compatible with 8 ohms
Internal Volume	25.7 L / 0.90 cu ft
Height, Width, Depth	93.8 cm x 16.5 cm x 29.8 cm
	36-15/16 in x 6-1/2 in x 11-3/4 in
Weight (Unpacked)	33.6 kg / 74 lb per pair
Finishes	Wengé, Cherry, Rosenut, Black Ash