



## Monitor 9

Design	4-driver, 2-1/2-way bass reflex, quasi-3rd-order resistive port
Crossover	3rd-order electro-acoustic at 1.9 kHz, 2nd-order electro-acoustic at 500 Hz (lower bass drivers)
High-Frequency Driver	25-mm (1 in) H-PTD™ dome, ferro-fluid cooled
Bass / Midrange Driver(s)	165-mm (6-1/2 in) M-ICP™ cone, 25-mm (1 in) voice coil, die-cast heatsink chassis
Bass Driver	Two 165-mm (6-1/2 in) carbon-infused polypropylene cones, 25-mm (1 in) voice coils, die-cast heatsink chassis
Low Frequency Extension	39 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 51 Hz - 20 kHz
30° Off-Axis	±2 dB from 51 Hz - 15 kHz
Sensitivity - Room / Anechoic	96 dB / 93 dB
Suitable Amplifier Power Range	15 - 200 watts
Maximum Input Power	150 watts
Impedance	Compatible with 8 ohms
Internal Volume	39.2 L / 1.38 cu ft
Height, Width, Depth	102.3 cm x 19 cm x 33.6 cm
	40-1/4 in x 7-1/2 in x 13-1/4 in
Weight (Unpacked)	39.9 kg / 88 lb per pair
Finishes	Wenge, Cherry, Rosenut, Black Ash