



Millenia™ 200

Design	6-driver, 2-1/2-way bass reflex, floorstanding design, MagneShield™††
Crossover	2nd-order electro-acoustic at 2.0 kHz, 2nd-order electro-acoustic at 800 Hz (bass drivers)
High-Frequency Driver	25-mm (1 in) S-PAL™ dome, die-cast chassis, ferro-fluid cooled
Bass / Midrange Driver(s)	Two 115-mm (4-1/2 in) MLP™ cones, 25-mm (1 in) dual-layer voice coils, HTD™ system die-cast heatsink chassis
Bass Driver	Three 115-mm (4-1/2 in) mineral-filled polypropylene cones, 25-mm (1 in) dual-layer voice coils, HTD™ system die-cast heatsink chassis
Low Frequency Extension	55 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 87 Hz - 20 kHz
30° Off-Axis	±2 dB from 87 Hz - 18 kHz
Sensitivity - Room / Anechoic	92 dB / 89 dB
Suitable Amplifier Power Range	15 - 150 watts
Maximum Input Power	130 watts
Impedance	Compatible with 8 ohms
Internal Volume	10.7 L / 0.38 cu ft
Height, Width, Depth	120 cm x 13 cm x 15 cm

	47-1/4 in x 5-1/8 in x 5-7/8 in
Weight	11.6 kg / 25.6 lb each
Finishes	Polished Aluminum, Black Chrome