



SA-35

Design	2-1/2-way in-wall / in-ceiling, 3-driver, die-cast chassis / mounting bracket
Crossover	3rd-order electro-acoustic at 2.0 kHz, 2nd-order electro-acoustic at 500 Hz (lower bass driver)
High-Frequency Driver	25-mm (1 in) G-PAL™ dome, die-cast heatsink, ferro-fluid cooled
Bass/Midrange Driver(s)	210-mm (8 in) S-PAL™ cone, 38-mm (1-1/2 in) voice coil, die-cast chassis
Bass Driver	210-mm (8 in) mineral-filled polypropylene cone, 38-mm (1-1/2 in) voice coil, die-cast chassis
Low Frequency Extension	34 Hz (DIN)
Frequency Rresponse on axis	±2 dB from 46 Hz - 22 kHz
Frequency Rresponse 30 off axis	±2 dB from 46 Hz - 20 kHz
Sensitivity-Room/Anechoic	96 dB / 92 dB
Suitable Amplifier Power Range	250 - 15 watts
Maximum Input Power	180 watts
Impedance	Compatible with 8 ohms
Height,Width or Diameter	51 cm x23.1 cm / 20-1/16 in x9-1/8 in (Height x Width)
Minimum Mounting Depth	7.6 cm /3 in
Cutout Dimensions	
Height x Width	19-1/8 in x 8-1/8 in (Height x Width)

Minimum Internal Volume Required	40 L / 1.4 cu ft
External dimensions	51 cm x 23.1 cm (Height x Width)
Pre-Installation Brackets	PB-8x19
Weight	31.3lb / 14.20kg
Finishes	White, paintable