



Studio 60

Design	4-driver, 2-1/2-way floorstanding
Crossover	2nd-order electro-acoustic at 2.0 kHz, 2nd-order electro-acoustic at 500 Hz (lower bass driver)
High-Frequency Driver	25-mm (1 in) G-PAL™ dome, die-cast heatsink chassis, ferro-fluid cooled, IMS / SHOCK-MOUNT™
Bass / Midrange Driver(s)	140-mm (5-1/2 in) S-PAL™ cone, 38-mm (1-1/2 in) voice coil, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Bass Driver	Two 140-mm (5-1/2 in) mineral-filled polypropylene cones, 38-mm (1-1/2 in) voice coil, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Low Frequency Extension	29 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 45 Hz - 22 kHz
30° Off-Axis	±2 dB from 45 Hz - 20 kHz
Sensitivity - Room / Anechoic	92 / 89 dB
Suitable Amplifier Power Range	15 - 220 watts
Maximum Input Power	170 watts
Impedance	Compatible with 8 ohms
Height, Width, Depth (Height includes spikes or outrigger feet)	101.8 cm x 20 cm x 30.1 cm 40-1/16 in x 7-7/8 in x 11-7/8 in

Weight	22.7 kg / 50 lb each
Finishes	Cherry, Rosenut, Black