



Studio ADP-590

Design	wall-mount bracket included, reverberant soundfield, 5-driver, 3-way surround / rear
Crossover	2nd-order electro-acoustic at 300 Hz (bass driver), 1st-order electro-acoustic at 2.1 kHz
High-Frequency Driver	Two 25-mm (1 in) G-PAL™ domes, die-cast heatsink chassis, ferro-fluid cooled, IMS / SHOCK-MOUNT™
Midrange Driver(s)	Two 89-mm (3-1/2 in) S-PAL™ cones, 25-mm (1 in) voice coils, ferro-fluid cooled, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Bass Driver	178-mm (7 in) mineral-filled polypropylene cone, 38-mm (1-1/2 in) voice coil, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Low Frequency Extension	60 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 85 - 20 kHz
30° Off-Axis	±(Reverberant Soundfield)
Sensitivity - Room / Anechoic	88 dB / 85 dB
Suitable Amplifier Power Range	15 - 180 watts
Maximum Input Power	130 watts
Impedance	Compatible with 8 ohms
Height, Width, Depth	22 cm x 37.5 cm x 17 cm

(Height includes spikes or outrigger feet) 8-11/16 in x 14-3/4 in x 6-11/16 in

Weight 7.7 kg / 17 lb each

Finishes Black, White

Paradigm® Stand (sold sep.) Paradigm® J-29, Paradigm® S-26